

4 Channels | E70.D4S

Piezo Controller



Characteristics >>

- 4 channels output
- Analog and digital control
- Small size, high output power
- High bandwidth
- Low ripple, servo control

Applications >>

- Driving piezo actuator
- Driving piezo nanopositioning stage
- Driving piezo objective scanner
- Driving piezo shifter
- Driving FTS fast tool positioner
- Driving piezo scanning platform
- Driving capacitive load

Introduction

This is a 4-channel piezoelectric controller with small size, high power, low power consumption, high bandwidth, and low ripple noise.

The controller adopts a dedicated operational amplifier circuit to ensure the output capability of high voltage and high current.



Harbin Core Tomorrow Science & Technology Co., Ltd.

Tel: +86-451-86268790

Email: info@coremorrow.com

Headquarters: Building I2, No.191 Xuefu Road, Nangang District, Harbin

Fax: +86-451-86267847


Web: www.coremorrow.com

Shanghai Office: Building 2, No.608 Shengxia Road, Pudong District, Shanghai

Technical Data >>

Type	E70.D4S
Functions	Digital & analog integrated controller
Channels	4
Nominal analog input(V)	-1.67~10
Nominal output voltage(V)	-20~120(optional -20~100/150)
Input power(W)	76
Peak current(A)	1/channel
Ave. current(mA)	70/channel
Bandwidth(Hz)	10k/channel
Bandwidth, 1/10(Hz)	10k/channel
Bandwidth(-3DB)(Hz)	37k/channel
Bandwidth, 1/10(-3DB)(Hz)	54k/channel
Ripple(mV)	5/channel (2.2μF)
PZT connector	ECG.0B.306.CLLV
Control input connector	SMB
Sensor type	SGS
Servo	P.I+low pass+notch filters
Sensor output connector	EPG.0B.305.HLN
Sensor output ripple(mV)	10
Communication	RS-232/422(D-SUB 9), USB(TYPE-C-female seat)
Baud rate	9600, 38400, 57600, 115200
Settable baud rate for software secondary development	9600, 19200, 38400, 57600, 76800, 115200, 128000, 230400, 256000
Processor	ARM 32 bit
D/A converter	16 bit±10V
A/D converter	16 bit±10V
PC software control function	Output voltage & displacement, waveform control, parameters set
PC software waveform control	Programmable/standard
Secondary development	VC++, Matlab, LabView & Program& DLL dynamic link library functions, etc.
Operating temperature(° C)	0~50
Over-current protection	Yes
Static power(W)	15
Cooling method	Fan
Size(mm) (L×H×D)	201×170×45.5
Mass(g)	1660
Power supply	24V DC4A
Power interface	DC-022B (Ø2.5)
Control way	Analog/digital signal


Curves >>




Disclaimer: The data here are typical, only for reference. Some variations will occur for different batch.

Panel Introduction >>


E70.D4S front panel




E70.D4S rear panel



Drawing >>



Driving Principle >>



Harbin Core Tomorrow Science & Technology Co., Ltd.

Tel: +86-451-86268790 Email: info@coremorrow.com
Fax: +86-451-86267847 Web: www.coremorrow.com

Headquarters: Building I2, No.191 Xuefu Road, Nangang District, Harbin
Shanghai Office: Building 2, No.608 Shengxia Road, Pudong District, Shanghai