

Linear Motion | N81.26K

Piezo Motor Driven Linear Actuator



Introduction

The linear piezo motor has the resolution of more than 20nm in full stroke, rated load of 30N, compact design, excellent long-term stability, and can continue to remain at the set position in the event of a power failure.

Characteristics >>

- Min step: <20 nm
- Compact design
- Self-locking at rest, requires no current
- Lifetime >1 x 10⁹ steps
- Optional vacuum version

Applications >>

- Stable adjustment in optical paths
- Long-term positioning
- Touch-free adjustment of hard-to-reach places
- Adjustment of optical frames



Harbin Core Tomorrow Science & Technology Co., Ltd.

Tel: +86-451-86268790 Email: info@coremorrow.com
Fax: +86-451-86267847 Web: www.coremorrow.com

Headquarters: Building I2, No.191 Xuefu Road, Nangang District, Harbin
Shanghai Office: Building 2, No.608 Shengxia Road, Pudong District, Shanghai

Technical Data >>

Type	N81.26K	Units
Travel	26	mm
Min. step	< 20	nm±20%
Load capacity	25	N
Speed	3	mm/min±10%
Position hold deviation at power up or down	<20	nm
Operating temperature ^[1]	10~40	°C
Mass with cable	85	g±5%
Material	Steel, Aluminum	
Cable length ^[1]	2	m±10mm
Voltage connector ^[1]	RJ11 4P4C	
PZT connector	RJ11	

Note: UHV version is available. Custom closed-loop version is available.

[1]: custom is available.


Optional Vacuum Version >>



>>

Drawing >>

Type	N81.26K
L	69.5mm



Recommended Controllers



E53.C4K

4 control interfaces, digital control
USB and serial port communication



Harbin Core Tomorrow Science & Technology Co., Ltd.

Tel: +86-451-86268790 Email: info@coremorrow.com
Fax: +86-451-86267847 Web: www.coremorrow.com

Headquarters: Building I2, No.191 Xuefu Road, Nangang District, Harbin
Shanghai Office: Building 2, No.608 Shengxia Road, Pudong District, Shanghai